



# MIGHTY EX6

### Refrigerator Body

| Engine                                      |                           |  |   |
|---|---------------------------|--|---|
| Type  | Turbo Charger Intercooler |  |   |
| 3.  |                           | 4 stroke-cycle, Water-cooled, Direct-injection diesel Engine |   |
| Number of Cylinder Piston Displacement (cc) |                           | 4 in-line<br>3.933cc   |   |
| Pistori Dispiacement (cc)                   |                           | Manual (5 Speed)   | Auto (6 Speed)  |
| Max. Power** ps/rpm (kw)                    | Furo V                    | 140ps/2,500 (102kw) Man                                      | 170ps/2,500 (125kw) Auto                              |
| Max. Torque ** (nm/rpm)                     | Euro V                    | 289/1,400 (392nm) Man  | 448/1,400 (608nm) Auto                                |
| Fuel System                                 | Injection pump            | Denso Common Rail System                                     | 140/1,400 (000/11/1) / 10/10                          |
| ,   |                           |  |   |
| Transmission                                |                           |  |   |
| Туре  |                           | Manual (5 Speed)   | Auto (6 Speed)  |
| Version                                     |                           | M035 \$ 5  | Allison 1000x fe                                      |
| Drive<br>Park Pawl                          |                           | Single Plate Clutch  | Lock up Torque Converter                              |
| PTO PTO                                     |                           | N/A  | YES Preperation for PTO                               |
| Permissable Torque                          |                           | Preperation for PTO<br>147 nm 2000 Rpm                       | 339 nm (min rpm 1200)                                 |
| Front Axle                                  |                           | 147 HHT 2000 KpHT  | 3341111 (11111111111200)                              |
| Type  |                           | Reverse Elliot type " I " beam                               |   |
| Capacity                                    | kg                        | 2760 kg  |   |
| Front Axle                                  | .,,                       |  |   |
| Capacity                                    | kg                        | 4700 kg  |   |
| Tyre & Wheel                                |                           |  |   |
| Туре  |                           | Single Front, Dual Rear                                      |   |
| Tyre  | Front / Rear              | 205/75R17.5-10PR   |   |
| Wheel                                       | Front / Rear              | 17.5 x 6.00  |   |
| Steering                                    |                           | Power Assisted   |   |
| Steering                                    |                           | Adjustable Steering Wheel                                    |   |
| Service Brake                               |                           | Adjustable Steering Wheel                                    |   |
| Front / Rear                                |                           | Disc/Disc  |   |
| Vehicle Dynamic Control (VDC)               |                           | (ESC) Electronic Stability Control, (ABS) A                  | anti Brake Skid, (HSA) Hill Start Assist,             |
| ,     |                           | (ESS) Emergency Stop Signal                                  |   |
| Parking Brake                               |                           |  |   |
| Actuation                                   |                           | Internal expanding type on Propeller shat                    | ft at the rear of Transmission assembly               |
| Exhaust Brake                               |                           |  |   |
| Type  |                           | Vacuum operated, Butterfly Valve type                        |   |
| Suspension                                  | Front / Rear              | Semi-elliptic, laminated Leaf Springs                        |   |
| Type<br>Shock absorber                      | FIUIII / Real             | Gas telescopic type on the FRONT/REAR                        | ayle  |
| Exhaust system                              |                           | das telescopie type on the intention                         | date  |
| General                                     |                           | Horizontal   |   |
| Fuel tank                                   |                           |  |   |
| Capacity                                    |                           | 100ℓ   |   |
| Frame                                       |                           |  |   |
| Туре  | ,                         |  | de rail & cross members, side rail is reinforced with |
| Main section side rail dimension            | (mm)                      | Depth x Flange x Thickness : 183 x 60 x 6                    | ot  |
| Weights                                     | Danas                     | CMD 2 OFOLG MAND 4 100kg (apray)                             |   |
| *Chassis cab weight kg                      | Range                     | SWB 3,950kg, MWB 4,100kg (aprox)<br>5,995 kg /6,500 kg       |   |
| ** Max Gross Vehicle Weight                 | Front (Door               | 2,760/4,700  |   |
| Gross vehicle weight Box Body               | Front /Rear               | 2,76074,700  |   |
| Туре  |                           | Hi Impact panel Pantech body                                 |   |
| Panel                                       |                           | Panel thickness 75mm, (optional upgrade                      | to 100mm)   |
| Dimension                                   |                           | Length 4300mm - Width 2230mm - Heig                          |   |
| Spec  |                           | 6 x Internal LED lights, Alloy plank floor, 2                |   |
| Rear Door                                   |                           | Dual Container style Rear Doors, (optional                   |   |
| Side Door                                   |                           | LH Side single Container Door ( width app                    |   |
| Rear bumper                                 |                           | Intergrated bumber step                                      |   |
|   |                           |  |   |

| Electrical system                   |   |
|-------------------------------------|---|
| Audio                               | M450 (Radio+Aux/MP3 USB) Multidisplay   |
| Auto Locking                        | Central Door Locking + Power Window + Keyless Entry + Semi Trim   |
| Steering Wheel Controls             | Bluetooth Phone - Audio - Cruise Control  |
| Head lamps                          | Semi-sealed Beam / Adjustable Dim   |
| Front Combination Lamps             | Turn signal / Hazard-Amber, Position - White  |
| Fog Lamps                           | White   |
| Rear Combination lamps              | Turn signal / Hazard-Amber, Tail / Stop - Red   |
| License Plate Lamp                  | White   |
| Service Lamp Circuit                | Yes   |
| Daytime Running Lights              | Yes   |
| 12v Socket in Dash                  | Yes x2  |
| Power Windows                       | Yes   |
| Back-up Lamp                        | White   |
| Instruments                         | Wille   |
| Meter Cluster                       | Fixed type  |
| Meter                               | Speedometer / Tachometer / Fuel gauge / Water temperature gauge LCD with odometer / Trip meter / Clock                |
| Warning Lamps & Indicators          | Brake fluid level of reservoir / Parking brake / Oil pressure / Battery charge /                                      |
| Walting Lamps & indicators          | Tell-tale lights for head light high beam / Turn signals / Door open / Seat belt / Low fuel                           |
| Ham                                 | Single, Electric  |
| Horn                                |   |
| Cruise Control                      | Yes   |
| Heating/ Air conditioning (Manual)  | Yes<br>Yes  |
| Steering Wheel Audio Remote Control | Yes   |
| Steering Wheel Auto Cruise Control  | Yes   |
| Body /Cab                           |   |
| Type Mounting                       | Tilt type with torsion bars, all steel welded construction with safety zone design Rigid or Semi floating type        |
| Windshield                          | One piece type with Laminated glass, Tinted upper section   |
| Windshield Wipers                   | Dual electric three speed (intermittent / low / fast) wipers & washer   |
| Mirrors                             | Mirror - Heated   |
| Driver's Seat                       | Coil Suspension, urethane foam cushioned STD trim   |
| Passenger's seat                    | Bench seat, STD Trim  |
| Steering Column                     | Fully Adjustable  |
| Roof Marker Lights                  | Yes   |
| Overhead Storage                    | Yes   |
| Mirror Width                        | Narrow STD (optional LONG)  |
| Active Safety Feautures             |   |
| Electronic Stability Control        | Yes   |
| ABS Braking                         | Yes   |
| Daytime Running Lights              | Yes   |
| Hill Start Assist                   | Yes   |
| Auto Headlights                     | Yes   |
| Bluetooth Hands Free                | Yes   |
| Heated Mirrors                      | Yes   |
| Warranty                            | 103   |
| Cab Chassis                         | 5 years or 300,000km (whichever occurs first) against manufactures defects  |
| Upper body                          | According to supplier   |
| Refrigeration (where applicable)    | Where applicable any refrigeration supplied will be either from Transcold or Thermo king, all warranty and service su |
| renigeration (where applicable)     | **************************************  |

#### nnotations

- 1) Empty vehicle weight and curb weight shown are to 3.5% variation to allow for production tolerance.
- 2) Empty vehicle weight and curb weight include weight of oil, fuel, coolant and spare tire carrier & bracket, but exclude standard tool set
- 3) The vehicle specification may differ per country.
- 4) Hyundai New Zealand reservs the right to alter the specifications, equipment or options or discontinue the models at any time without prior notice.


be according to their terms and conditions

- \*Approximate, depending on variant and specification
- \*\*Max GVW includes the front and rear axle loads based on permissable tyre load 5,995kg & 6,500kg varients
- images may contain additional cost options

# MIGHTY EX6

### **Refrigerator Body**

EX6 Std Cab MWB W/B: 3400



#### Please Note:

- -All drawings are indicative and may show additional cost options
- -All measurements should be viewed as approximate measurements
- -Internal measurements shown are wall to wall or floor to ceiling, door entrances and floor may have a reduced measurement due to construction requirements
- -Dimensions shown are a standard specification however build to order custom specifications are available on request